

## CONDUMAX II TRANSPORTABLE

Transportable natural gas dew-point analyzer system for operation in the field. Suitable for IEC Zone 1 or 2 hazardous area, NEC Class I, Division 1 Groups B, C, D

Product Parent Code: CD2PSS Condumax II Transportable, Hydrocarbon Dew-Point Analyzer		
Feature	Item	Description
Feature {A}	<b>Base Model</b>	
	CD2PSS-AT-HW-MC	ATEX certified, automatic, Transportable HC and water DP (ISO18453) in natural gas analyser with built in sample system. (230 VAC). Chilled mirror, 0.5C HCDP accuracy. Capacitive touch screen, pressure reading, flow alarm, Modbus RTU, two 4-20mA outputs. Max. 100 barg, flow rate 0.06 m3/h (1 L/min)
	CD2PSS-CS-HW-MC	CSA certified, automatic, Transportable HC and water DP (IGT #8) in natural gas analyser with built in sample system. (110 VAC). Chilled mirror, 0.5C HCDP accuracy. Capacitive touch screen, pressure reading, flow alarm, Modbus RTU, two 4-20mA outputs. Max. 100 barg, flow rate 0.06 m3/h (1 L/min)

## CONDUMAX II TRANSPORTABLE ACCESSORIES, SPARE PARTS, DOCUMENTATION & SERVICES

Order Codes	Product / Description
<b>Spares &amp; Accessories</b>	
SSF-CF-LON-10PK	Coalescing Filter Cartridge (pack of 10)
CD2PSS-OPJB	Optional outputs junction box
CD2-SCR-002	HC dew-point sensor cell assembly (with Storm pressure transmitter)
CD2-WDC-002	Water dew-point sensor assembly (with Storm pressure transmitter)
CD2-SX-WDC-002	Water dew-point sensor exchange (fully calibrated)
<b>Documentation (Standard documentation package comprises User Manuals (one printed per analyzer system) plus CD ROM containing Ex certificates, Drawing Set, Calibration Certificates and Pressure test certificates)</b>	
* SP-MC	Material Certificates for spare parts
<b>Packaging</b>	
* CD2PSS-PAC	Packing for Condumax II transportable (for air and road)
<b>Additional Services</b>	
** CD2-FAT1	One day FAT pre-delivery inspection / or first day of inspection
** CD2-FAT2	Each consecutive day of FAT pre-delivery inspection
** GEN-FAT-ST8	FAT 8 hour stability test
** GEN-FAT-ST12	FAT 12 hour stability test
** GEN-FAT-ST24	FAT 24 hour stability test
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>	
<b>** These are the Michell charges for the FAT only. The cost of any third party inspector attending will be passed on, at cost, in addition to the Michell charges. Therefore, please ensure that the costs of any third party inspector(s) are added at the quotation stage.</b>	

Please note: Michell Instruments adopts a continuous development program which sometimes necessitates specification changes without notice. Please contact us for latest version. Issue No: Condumax II Transportable\_97149\_V5\_UK\_0223