



Model Number 130A25	ICP® ELECTRET ARRAY MICROPHONE			Revision: NR ECN #: 50628
Performance Nominal Microphone Diameter Frequency Response Characteristic(at 0° incidence) Frequency Response(± 2 dB) Frequency Response(± 3 dB) Frequency Response(± 4 dB) Phase Match(100 Hz to 3 kHz) Phase Match(50 Hz to 5 kHz) Phase Match(5 kHz to 10 kHz) Sensitivity Sensitivity(+/- 3)(@ 250 Hz) Inherent Noise(Linear) Inherent Noise(A Weighted) Inherent Noise(A Weighted) Dynamic Range(3% Distortion Limit) TEDS Compliant	ENGLISH 1/4" Free-Field 20 to 10,000 Hz 10 to 16,000 Hz 10 to 20,000 Hz ± 3° ± 5° ± 10° 45 mV/Pa -26.9 dB re 1 V/Pa 29 dB re 20 µPa < 26 dB(A) re 20 µPa 24 dB(A) re 20 µPa 122 dB re 20 µPa Yes	SI 1/4" Free-Field 20 to 10,000 Hz 10 to 16,000 Hz 10 to 20,000 Hz ± 3° ± 5° ± 10° 45 mV/Pa -26.9 dB re 1 V/Pa 29 dB re 20 µPa < 26 dB(A) re 20 µPa 24 dB(A) re 20 µPa 122 dB re 20 µPa Yes		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Environmental Temperature Range(Operating) Temperature Effect on Output(- 10 to +50 °C)	+14 to +122 °F 0.7 dB	-10 to +50 °C 0.7 dB	[1]	
Electrical Excitation Voltage Constant Current Excitation Output Bias Voltage Output Impedance	18 to 30 VDC 2 to 20 mA 5.5 to 14 VDC < 150 Ohm	18 to 30 VDC 2 to 20 mA 5.5 to 14 VDC < 150 Ohm		
Physical Housing Material Electrical Connector(Output) Size (Diameter x Length)(overall) Weight	Stainless Steel 10-32 0.28 in x 1.35 in 0.19 oz	Stainless Steel 10-32 7.0 mm x 34.4 mm 5.3 gm	[1]	
	NOTES: [1]Typical. [2]TEDS Capable Digital Communication, compliant with IEEE 1451.4 [3]See PCB Declaration of Conformance PS023 for details.			
Entered: LK	Engineer: MJN	Sales: MV	Approved: NJF	Spec Number:
Date: 03/24/2020	Date: 03/24/2020	Date: 03/24/2020	Date: 03/24/2020	72403
 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043				
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Piezotronics, Inc.				