


Piezoresistive pressure transducer

Model 8530B



STANDARD TOLERANCE

INCHES	[MILLIMETERS]
.XX = ± .03	[X = ± .8]
.XXX = ± .010	[.XX = ± .25]

Key features

- 200, 500, 1000 and 2000 psia ranges
- Absolute reference
- 300mV full scale output
- Rugged, miniature

Description

Model 8530B is a miniature, high sensitivity piezoresistive pressure transducer for measuring absolute pressure. The volume behind the diaphragm is evacuated and glass sealed to provide an absolute pressure reference. Full scale output is 300 mV with high overload capability and high frequency response. It is available in ranges from 200 psia to 2000 psia. See model 8530C for lower pressure ranges.

Endevco® pressure transducers feature an active four arm strain gage bridge diffused into a sculptured silicon diaphragm for maximum sensitivity and wideband frequency response. Self-contained hybrid temperature compensation provides stable performance over the temperature range of 0°F to 200°F (-18°C to +93°C). Endevco's brand transducers also feature excellent linearity, high shock resistance, and high stability during temperature transients.

Piezoresistive pressure transducer | Model 8530B

The following performance specifications conform to ISA-RP-37.2 (1964) and are typical values, referenced at +75°F (+24°C) and 100 Hz, unless otherwise noted. Calibration data, traceable to National Institute of Standards and Technology (NIST), is supplied.

Specifications					
Dynamic characteristics	Units	-200	-500	-1000	-2000
Range	psia	0–200	0–500	0–1000	0–2000
Sensitivity	mV/psi	1.5 ±0.5	0.6 ±0.2	0.3 ±0.1	0.3 ±0.1
Combined: non-linearity, non repeatability, pressure hysteresis [1]	% FSO RSS max	0.5	0.5	1	1
Non-linearity, independent	% FSO typ	0.2	0.2	0.2	0.2
Non-repeatability	% FSO typ	0.1	0.1	0.1	0.1
Pressure hysteresis	% FSO typ	0.1	0.1	0.1	0.1
Zero measurand output	mV max	±20	±20	±20	±20
Zero shift after 3X over range	±% 3X FSO max (typ)	0.2 (0.05)	0.2 (0.05)		
after 2.5X over range	±% 2.5X FSO max (typ)			0.2 (0.1)	
after 1.5X over range	±% 1.5X FSO max (typ)				0.2 (0.1)
Thermal zero shift					
From 0 to 200°F (-18°C to +93°C)	±% FSO max	3	3	3	3
Thermal sensitivity shift					
From 0 to 200°F (-18°C to +93°C)	±% max	4	4	4	4
Resonant frequency	Hz	750 000	1 000 000	> 1 000 000	> 1 000 000
Non-linearity at 3X over range	% 3X FSO	1.5	2	2.0 @ % 2.5X FSO	2.0 @ % 1.5X FSO
Thermal transient response per	psi / °F	0.02	0.02	0.04	0.04
ISA-S37.10, PARA. 6.7, procedure I	psi / °C	0.04	0.04	0.07	0.07
Photoflash response [2]	equiv psi	5	10	20	20
Warm-up time [3]	ms	1	1	1	1
Acceleration sensitivity	equiv. psi/g	0.0003	0.0002	0.0002	0.0002
Burst pressure (diaphragm)	psia min	800	2000	4000	4000
Case pressure [4]	psia min	1000	5000	5000	5000
Electrical characteristics					
Supply voltage [5]	10.0 Vdc standard, 18 Vdc maximum				
Electrical configuration	Active four-arm piezoresistive bridge				
Polarity	Positive output for increasing pressure				
Resistance					
Input	2000 ±800 ohms				
Output	1500 ±600 ohms				
Isolation	100 megohms minimum at 50 Volts, leads to case, leads to shield, shield to case				
Noise	5 microvolts rms typical, DC to 50 000 Hz; 50 microvolts rms maximum, DC to 50 000 Hz				
Physical characteristics					
Case, material	Stainless steel (17-4 PH CRES)				
Cable, integral	Four conductor No. 32 AWG Teflon insulated leads, braided shield, silicone jacket				
Dead volume port (+)	0.0003 cubic inches (0.005 cc)				
Mounting/torque	10-32 UNF-2A threaded case 0.438 inch (11.12 mm) long / 15 ±5 lbf-in (1.7 ±0.6 Nm)				
Weight	2.3 grams (cable weighs 9 grams/meter)				
Media [6] [7]	Clean dry gas. Contact factory for protective modifications for other media.				
Operating temperature	-65°F to +250°F (-54°C to +121°C)				
Vibration	1000 g pk				
Acceleration	1000 g				
Shock	20 000 g, 100 microsecond haversine pulse				
Humidity	Isolation resistance greater than 100 megohms at 50 V when tested per MIL-STD-202E, method 103B, test condition B				


Piezoresistive pressure transducer | Model 8530B

Accessories		
Options	Description	8530B
EHR93	O-ring, Viton	Included
EHR96	O-ring, fluorosilicone	Optional

Other options		
Options	Description	
M5	Metric thread	
M6	No screen	
M8	"B" screen, black grease	
M9	"A" screen, black grease	
M37	Integral connector	

Notes

- FSO (Full Scale Output) is defined as transducer output change from 0 to + full scale pressure.
- Per ISA-S37.10, Para. 6.7, Proc. II.
- Warm-up time is defined as elapsed time from excitation voltage "turn on" until the transducer output is within $\pm 1\%$ of reading accuracy.
- Case pressure identifies media containment pressure in the event of diaphragm rupture.
- 10 Vdc excitation voltage is standard. For sensitivity and ZMO at 5V excitation, include -D in the part number as per Note 10.
- Internal seals are epoxy and are compatible with clean dry gas media. Media in measurand port is exposed to CRES, Parylene C, epoxy and the Viton O-ring. Not suitable for use with high pH or low pH liquids, long term exposure to water, or exposure to solvents which may attack epoxies.
- O-ring, Parker 5-125, compound V747-75 (Viton®) is supplied unless otherwise specified on purchase order. Fluorosilicone O-ring, for leak tight operation below 0°F is available on special order.
- Maintain high levels of precision and accuracy using Endevco's factory calibration services. Call Endevco's inside sales force at 866-ENDEVCO for recommended intervals, pricing and turn-around time for these services as well as for quotations on our standard products.
- Model number definition:



10869 NC Highway 903, Halifax, NC 27839 USA

endevco.com | sales@endevco.com | 866 363 3826

© 2024 PCB Piezotronics - all rights reserved. PCB Piezotronics is a wholly-owned subsidiary of Amphenol Corporation. Endevco is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevco), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at www.pcb.com/trademarkownership.