



### Key Features:

- **Full Frame Rate Streaming** Experience unmatched image clarity and speed with 10 GigE, CXP 2.1, and CameraLink Full high-speed interfaces
- **Extended SSD Recording** Capture more than 1.5 hours of detailed thermal events directly to a 4 TB SSD with zero dropped frames.
- **Seamless Data Integration** Effortlessly transfer full recordings from SSD to computer, ensuring your thermal data is always ready for analysis.
- **Precise Timing System** Proprietary triggering, synchronization, and accurate IRIG time stamping system that ensures precise, on-time recording.

### Main Applications:

- Ballistics and munitions testing
- Target signature
- Radiometry
- Airbag testing
- Non-destructive testing

[www.FLIR.com/X6980HS](http://www.FLIR.com/X6980HS)

### SPECIFICATIONS

	X6980HS	X6981HS	X6982HS	X6983HS
Part #	29447-280	29447-281	29447-282	29447-283
<b>Detector</b>				
Detector Type	FLIR Indium Antimonide (InSb)			
Spectral Range	1.5 – 5.0 $\mu\text{m}$	3.0 – 5.0 $\mu\text{m}$	1.5 – 5.0 $\mu\text{m}$	3.0 – 5.0 $\mu\text{m}$
Camera f/#	f/2.5	f/2.5	f/4.1	f/4.1
Resolution	640 × 512			
Detector Pitch	25 $\mu\text{m}$			
Thermal Sensitivity/ NETD, typical	20 mK, typical			
Operability	≥99.5% (≥99.95% typical)			
Sensor Cooling	Closed cycle rotary			
<b>Electronics</b>				
Readout Type	Snapshot			
Readout Modes	Asynchronous Integrate While Read; Asynchronous Integrate Then Read			
Synchronization Modes	Sync In, Sync Out, Tri-Level Sync, Video Sync			
Image Time Stamp	Internal precision timestamp. IRIG-B AM decoder, TSPI accurate, Free wheel if sync signal is lost			
Trigger Modes	Trigger In, Software generated, Time generated			
Integration Time	270 ns to approx. Full Frame			
Pixel Clock	355.2 MHz			
Frame Rate (Full Window)	Programmable; 0.0015 Hz to 1004 Hz			
Subwindow Mode	Flexible windowing down to 32 × 4 (steps of 32 columns, 4 rows)			
Dynamic Range	14-bit			

For more information and to find your local support number, visit:  
[FLIR.com/contact/instruments-support](http://FLIR.com/contact/instruments-support)  
[www.FLIR.com](http://www.FLIR.com)

©2024 Teledyne FLIR, LLC. All rights reserved.  
 Revised 03/21/24  
 FLIR X6980-HS\_INSB\_a4



# FLIR X6980-HS INSB™

High-Speed MWIR  
Science-Grade Camera

## SPECIFICATIONS, CONT.

	X6980HS	X6981HS	X6982HS	X6983HS
<b>Electronics Continued</b>				
Direct to SSD Recording	Yes, removable 4 TB NVMe SSD included, approx. 2 hours of zero dropped frames record time			
On-Camera Image Storage	RAM (volatile): 64 GB, up to 95,000 frames full frame NVMe U.2 SSD (user-removable/non-volatile): 4 TB U.2 SSD included, up to 6 M frames full frame			
Download of On-Camera RAM/SSD Recordings	Transfer from SSD through 10 GigE, CXP, or CL to Research Studio			
Radiometric Data Streaming	Simultaneous 10 Gigabit Ethernet (GigE Vision), Camera Link Full, CoaXPress (CXP 2.1) Single link @ 10GBPS or Dual Link @ 5GBPS			
Standard Video	HDMI, SDI			
Command and Control	GigE, USB, RS-232, Camera Link, CXP (GenICam protocol supported over GigE or CXP)			
<b>Temperature Measurement</b>				
Standard Temperature Range (with band matched optics)	-20°C to 300°C (-4°F to 572°F)	-20°C to 350°C (-4°F to 662°F), -10°C for microscopes	-20°C to 350°C (-4°F to 662°F)	-20°C to 350°C (-4°F to 662°F), -10°C for microscopes
Optional Temperature Range (with band matched optics)	45°C to 600°C (ND1) 250°C to 2000°C (ND2) 500°C to 3000°C (ND3)			
Accuracy	≤100°C ±2°C (±1°C typical), > 100°C ±2% of reading (±1% typical)			
Ambient Drift Compensation (with factory cal)	Yes			
<b>Optics</b>				
Available Lenses	Manual (broadband): 25 mm, 50 mm, 100 mm Motorized (broadband): 25 mm, 50 mm, 100 mm	Manual (3.0 – 5.0 μm): 17 mm, 25 mm, 50 mm, 100 mm, 200 mm, Macro Motorized (3.0 – 5.0 μm): 17 mm, 25 mm, 50 mm, 100 mm, 200 mm	Manual (broadband): 25 mm, 50 mm, 100 mm Motorized (broadband): 25 mm, 50 mm, 100 mm	Manual (3.0 – 5.0 μm): 17 mm, 25 mm, 50 mm, 100 mm, 200 mm, 50mm Macro Motorized (3.0 – 5.0 μm): 17 mm, 25 mm, 50 mm, 100 mm, 200 mm
Close-up Lenses/Microscopes	No microscopes available	1x, 3x	No microscopes available	1x, 3x, 5x, 1 × 20 cm LWD
Lens Interface	FLIR FPO-M (4-tab bayonet, motorized)			
Focus	Motorized (compatible w/ manual)			
Filtering	4-position motorized filter wheel, standard 1-inch filters, user swappable			
<b>Image/Video Presentation</b>				
Palettes	Selectable 8-bit			
Automatic Gain Control	Manual, Linear, Plateau equalization, DDE			
Overlay	Customizable with the ability to toggle off			
Video Modes	HD-SDI: 720p@50/59.9 Hz, 1080p@25/29.9 Hz, 1080p@60 Hz SD-SDI: 480i@60 Hz, 576i@50 Hz			
Digital Zoom	1x, Auto (best fit)			
<b>General</b>				
Operating Temperature Range	-20°C to 50°C (-4°F to 122°F)			
Power	24 VDC (<50 W steady state)			
Weight w/o Lens	6.35 kg (14 lbs)			
Size (L × W × H) w/o Lens	249 mm × 157 mm × 147 mm (9.8 in × 6.2 in × 5.8 in)			
Mounting	2 × ¼ in. -20, 1 × 3/8 in. -16, 4 × #10 -24, Side: 3 × ¼ in. -20 (each side)			

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).

For more information and to find your local support number, visit:  
**FLIR.com/contact/instruments-support**  
**www.FLIR.com**

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.  
For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2024 Teledyne FLIR, LLC. All rights reserved.  
Revised 03/21/24  
FLIR X6980-HS\_INSB\_a4  
(24-0023-INS)

Aufgrund laufender Weiterentwicklungen sind Änderungen der Spezifikationen vorbehalten. Alle Angaben vorbehaltlich Satz- und Druckfehler.

**nbn Austria GmbH**

Riesstraße 146, 8010 Graz

+43 316 40 28 05

[info@nbn.at](mailto:info@nbn.at) | [www.nbn.at](http://www.nbn.at)

